

## 스테인리스 스트레이너(1MPa) - SCREWED TYPE



Model		
Applicable Fluid		Water, Oil, Gas
Working Pressure		Less than 1.0Mpa
Suitable Temperature		180℃
Connection Method		PT Screwed
Test		1.5Mpa(water)
Material	Body	SSC13, SSC14
	Trim	STS304

  

Size	L	H
15	60.3	60
20	73	75
25	86.5	90
32	100	100
40	108	120
50	138	148

## 스테인리스 스트레이너(1MPa) - S. B TYPE



Model		
Applicable Fluid		Water, Oil, Gas
Working Pressure		Less than 1.0Mpa
Suitable Temperature		180℃
Connection Method		10K Flange
Test		1.5Mpa(water)
Material	Body	SSC13, SSC14
	Trim	STS304

  

Size	L	H
15	130	108
20	145	117
25	150	133
32	160	152
40	182	196
50	200	191
65	268	224
80	287	250
100	340	296

## 스테인리스 스트레이너(1MPa) - B. B TYPE



Model		
Applicable Fluid		Water
Working Pressure		Less than 1.0Mpa
Suitable Temperature		180℃
Connection Method		10k Flange
Test		1.5Mpa(water)
Material	Body	SSC13, SSC14
	Trim	STS304

  

Size	L	H
65	250	242
80	280	272
100	310	316
125	350	349
150	380	396
200	500	498