



MODEL NST-OKV1



ÖZEL TEKNİK ŞARTLARI / SPECIFICATION & TECHNICAL CONDITIONS

NORMAL BASINÇ / NOMINAL PRESSURE	PN16,25,40,64,100
AKIŞ KARAKTERİSTLİĞİ / FLOW CHARACTERISTIC	EQUAL PERCENTAGE, LINEAR, QUICK OPEN (For Shut-Off valve)
KAPAK BİÇİMİ / BONNET FORM	Standart Type: Cast Steel : -20~250° C Cast Stainless steel: -40~250° C
	Fin-Extension Type : Cast Steel: -29~425 Cast Stainless Steel : 40~450° C
	Long-Extension Type: Cast Steel: -60~-100° C, -100~-200, 200~-250° C
SİT SIZDIRMAZLIĞI / SEAT SEALING	ANSI IV, V, VI (Soft Sealing)

NO	PARÇA ADI / PART NAME	MALZEME / MATERIAL
1	GÖVDE / BODY	GJS-400-18-LT/395 / WCB / CF8 / CF8M
2	KLAPE / FLAP	1.4305 ~ PEEK
3	SİT / SEAT	1.4305
4	BOYUNLUK / CAGE	GGG40
5	KLAVUZ KOVANI / GUIDE SLEEVE	1.4104
6	MİL / SHAFT	1.4305
7	KAPAK / BONNET	GJS-400-18-LT/395
8	POZİSYONER / POSITIONER	OPSİYONEL
9	AKTÜATÖR / ACTUATOR	ERD 6224
10	V PAKET CONTA / V PACKET GASKET	PTFE / CARBON

AKIŞ KARAKTERİSTLİĞİ / FLOW CHARACTERISTIC

SEAT DIAMETER DN(MM)	DN15	DN20	DN25	DN32	DN40	DN50	DN65	DN80	DN100	
RATED Kv	LINEAR	4	6,3	10	16	25	40	60	80	160
	EQ%									

PN16 DIN 2501

ÖLÇÜ / SIZE	L	H2	H3	Ø	AĞIRLIK / WEIGHT KGS
DN15	130	107	216	240	14,5
DN20	150	107	216	240	15,1
DN25	160	107	216	240	15,6
DN32	180	99	225	270	20,2
DN40	200	99	225	270	21
DN50	230	99	225	270	22,7
DN65	290	162	228	270	34,3
DN80	310	162	228	270	36
DN100	350	197	333	380	64

PNÖSAN San ve Tic. Ltd. Şti.

Merkez : Cemaliye Mah. Gazi Çeşme Sok. No: 2/A 59860 Çorlu / TEKİRDAĞ

Tel: (+90 282) 652 94 86 Pbx Fax: (+90 282) 652 74 05

Fabrika : Zafer Mah. Bakım Onarım 6. Sk. No: 54-55-56 Çorlu / TEKİRDAĞ

www.pnosan.com.tr / bilgi@pnosan.com.tr / satis@pnosan.com.tr